

L^AT_EX News

Issue 21, May 2014 (L^AT_EX release 2014-05-01)

Scheduled L^AT_EX bug-fix release

This issue of L^AT_EX News marks the second bug-fix release of L^AT_EX 2_ε (standard L^AT_EX) since shifting to a new build system in 2009. Provided sufficient changes are made, we expect to make such releases yearly or every two years, in sync with T_EX Live.

Release notes

This release makes no changes to the core code in the L^AT_EX 2_ε format but there are a small number of documentation fixes (not listed here). In addition several packages in the **base** and **required** areas have been updated as detailed below.

This has been done in accordance with the philosophy of minimising problems in both forwards and backwards compatibility, so most of these changes should not be noticed by the regular L^AT_EX user.

References in the text below of the form “graphics/3873” are to bug reports listed at: <http://latex-project.org/cgi-bin/ltxbugs2html>

fixltx2e updates

There are a number of bugs and faulty design decisions in L^AT_EX 2_ε that should have been corrected long ago in the kernel code. However, such corrections cannot be done as this would break backwards compatibility in the following sense. A large number of documents exist by now that have worked around the bug or have even made use of a particular misfeature. Thus changing the kernel code would break too many existing documents.

The corrections for these types of bug have therefore been collected together in a package that can be loaded only when needed; its name is `fixltx2e`. For this release we made the following changes to this package:

- Misspelled float placement specifiers such as `\begin{figure}[tv]` instead of `tb` are silently ignored by the kernel code. Now we test for such letters and issue an error message.
- L^AT_EX’s float handling algorithm can get out of sync if you mix single and double-column floats (as they are placed independently of each other). This was corrected in `fixltx2e` a few years ago but the fix was not perfect as one situation using `\enlargethispage` generated a low-level T_EX error. This behaviour of the package is now improved.

New fltrace package

For years the file `ltoutput.dtx` contained some hidden code to trace the detailed behaviour of the float placement algorithm of L^AT_EX. Prompted by questions on StackExchange we now extract this code into a new `fltrace` package. To see the float algorithm in action (or to understand why it decides to place all your floats at the very end of the document) use

```
\usepackage{fltrace} \tracefloats
```

To stop tracing somewhere in the document use `\tracefloatsoff` and to see the current value of various float parameters use `\tracefloatvals`. As the package is identical to the kernel code with tracing added, it may or may not work if you load any other package that manipulates that part of the kernel code. In such a case your best bet is to load `fltrace` first.

inputenc package updates

The `inputenc` package allows different input encodings for L^AT_EX documents to be specified including the important `utf8` option used to specify the Unicode UTF-8 encoding. A common mistake in documents has been to also include this option when using the Unicode-based T_EX engines LuaT_EX and X_ƎT_EX producing strange errors as these engines natively deal with UTF-8 characters.

If a document stored in an 8bit encoding is processed by pdfT_EX, it needs the `inputenc` package to work correctly. However, if such a document is processed unchanged by LuaT_EX or X_ƎT_EX, then accented characters may silently get dropped from the output.

The package has been modified so that if used with LuaT_EX or X_ƎT_EX, then it just issues a warning if `utf8` or `ascii` is specified, and stops with an error for any other encoding requested.

One further improvement has been made to the encoding definition files (`.def`) used by `inputenc`: the catcode of `@` is now saved and restored when reading them instead of always using `\makeatother` inside the files (`latex/4192`).

The tools directory

In the past each of the sub-directories in the “required” section of the L^AT_EX distribution contained a single `.ins` file to generate the code files from the source files. We have now started to provide individual `.ins` files for each of those packages that are likely to require updates outside a major L^AT_EX release.

multicol updates

Version 1.8 of `multicol` implements some improvements/fixes and one extension. In the past the balancing algorithm enlarged the column height until it found a solution that satisfied all constraints. If there were insufficient break points then the final column height could have been much larger than expected and if that happened near the end of the page it resulted in the text overflowing into the bottom margin. This situation is now detected and in that case a normal page is cut and balancing is resumed on the next page. Some overflow is still allowed and controlled via the parameter `\maxbalancingoverflow`.

The use of `\enlargethispage` is now properly supported within the environment. Finally a new command `\docolaction` was added to allow the execution of code depending on the column in which the command is executed. See the documentation for details.

Bug fixes: the new version fixes both a color leak that could happen in certain situations and the problem that `multicols` could mess up the positioning of `\marginpars` that followed the environment.

tabularx updates

The restrictions on embedding `\tabularx` `\endtabularx` into the definition of a new environment have been relaxed slightly. See the package documentation for details.

showkeys updates

The `showkeys` package has been updated to fix problems if used at the start of list items, and to work if brace groups (`{` and `}`) are used in the optional argument of `\cite`. ([tools/4162](#), [tools/4173](#))

color updates

The `\nopagecolor` command suggested by Heiko Oberdiek, available for some years in the `pdftex` option, has been added to the core package as suggested in [graphics/3873](#). Currently this is supported in the driver files for `dvips` and `pdftex`. Patches to support other drivers are welcome.

graphicx updates

The `graphicx` version of `\rotatebox` now allows `\par` (and blank lines) in values, to match the change made to the `graphics` version some years ago. See [graphics/4296](#).

keyval updates

All parsing used in the `keyval` package has been changed to allow `\par` (and blank lines) in values. (A second change, to parsing of brace groups in a construct such as `key={{value}}`, was reverted in v1.15.) See [graphics/3446](#).

Standard L^AT_EX (L^AT_EX 2_ε) and expl3

The substantial collection of innovative code in `expl3` implements a new programming language that has for a while now been used by some writers of L^AT_EX 2_ε packages. This code has recently also been made available for use on top of plain T_EX or ConT_EXt, largely to support generic packages that are supposed to work with different flavours of T_EX. These uses in no way affect authors of L^AT_EX documents and such L^AT_EX 2_ε packages will continue to work as advertised by their authors with standard L^AT_EX.

This code base will also become an important foundation for the kernel of L^AT_EX 3 and so the new programming language can be described as ‘The L^AT_EX 3 Programming Language’. However, if you see or hear that a package ‘uses L^AT_EX 3’ then it remains very unlikely (as yet) to mean that the package is part of some ‘new version of L^AT_EX’.

News about the development and use of `expl3` and about other developments in the L^AT_EX 3 code base is reported regularly in the L^AT_EX 3 News series (<http://latex-project.org/13news/>), the most recent issue of which was published in March 2014.