

Internet Engineering Task Force (IETF)  
Request for Comments: 5998  
Updates: 5996  
Category: Standards Track  
ISSN: 2070-1721

P. Eronen  
Independent  
H. Tschofenig  
Nokia Siemens Networks  
Y. Sheffer  
Independent  
September 2010

## An Extension for EAP-Only Authentication in IKEv2

### Abstract

IKEv2 specifies that Extensible Authentication Protocol (EAP) authentication must be used together with responder authentication based on public key signatures. This is necessary with old EAP methods that provide only unilateral authentication using, e.g., one-time passwords or token cards.

This document specifies how EAP methods that provide mutual authentication and key agreement can be used to provide extensible responder authentication for IKEv2 based on methods other than public key signatures.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc5998>.

## Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

## 1. Introduction

The Extensible Authentication Protocol (EAP), defined in [RFC3748], is an authentication framework that supports multiple authentication mechanisms. Today, EAP has been implemented at end hosts and routers that connect via switched circuits or dial-up lines using PPP [RFC1661], IEEE 802 wired switches [IEEE8021X], and IEEE 802.11 wireless access points [IEEE80211i].

One of the advantages of the EAP architecture is its flexibility. EAP is used to select a specific authentication mechanism, typically after the authenticator requests more information in order to determine the specific authentication method to be used. Rather than requiring the authenticator (e.g., wireless LAN access point) to be updated to support each new authentication method, EAP permits the use of a backend authentication server that may implement some or all authentication methods.

IKEv2 ([RFC4306] and [RFC5996]) is a component of IPsec used for performing mutual authentication and establishing and maintaining Security Associations (SAs) for IPsec ESP and Authentication Header (AH). In addition to supporting authentication using public key signatures and shared secrets, IKEv2 also supports EAP authentication.

IKEv2 provides EAP authentication since it was recognized that public key signatures and shared secrets are not flexible enough to meet the requirements of many deployment scenarios. By using EAP, IKEv2 can leverage existing authentication infrastructure and credential databases, since EAP allows users to choose a method suitable for existing credentials, and also makes separation of the IKEv2 responder (VPN gateway) from the EAP authentication endpoint (backend Authentication, Authorization, and Accounting (AAA) server) easier.

Some older EAP methods are designed for unilateral authentication only (that is, EAP peer to EAP server). These methods are used in conjunction with IKEv2 public-key-based authentication of the responder to the initiator. It is expected that this approach is especially useful for "road warrior" VPN gateways that use, for instance, one-time passwords or token cards to authenticate the clients.

However, most newer EAP methods, such as those typically used with IEEE 802.11i wireless LANs, provide mutual authentication and key agreement. Currently, IKEv2 specifies that these EAP methods must also be used together with responder authentication based on public key signatures.

In order for the public key signature authentication of the gateway to be effective, a deployment of Public Key Infrastructure (PKI) is required, which has to include management of trust anchors on all applicants. In many environments, this is not realistic, and the security of the gateway public key is the same as the security of a self-signed certificate. Mutually authenticating EAP methods alone can provide a sufficient level of security in many circumstances, and in fact, in some deployments, IEEE 802.11i uses EAP without any PKI for authenticating the Wireless Local Area Network (WLAN) access points.

This document specifies how EAP methods that offer mutual authentication and key agreement can be used to provide responder authentication in IKEv2 completely based on EAP.





If the responder supports this notification and chooses to use it, it omits the public-key-based AUTH payload and CERT payloads from message 4.

If the responder does not support the EAP\_ONLY\_AUTHENTICATION notification or does not wish to use it, it ignores the notification payload, and includes the AUTH payload in message 4. In this case, the initiator MUST verify that payload and any associated certificates, as per [RFC4306].

When receiving message 4, the initiator MUST verify that the proposed EAP method is allowed by this specification, and MUST abort the protocol immediately otherwise.

Both the initiator and responder MUST verify that the EAP method actually used provided mutual authentication and established a shared secret key. The AUTH payloads sent after EAP Success MUST use the EAP-generated key, and MUST NOT use SK\_pi or SK\_pr (see Section 2.15 of [RFC5996]).

An IKEv2 message exchange with this modification is shown below:

Initiator	Responder
-----	-----
HDR, SAi1, KEi, Ni, [N(NAT_DETECTION_SOURCE_IP), N(NAT_DETECTION_DESTINATION_IP)] -->	<-- HDR, SAr1, KEr, Nr, [CERTREQ], [N(NAT_DETECTION_SOURCE_IP), N(NAT_DETECTION_DESTINATION_IP)]
HDR, SK { IDi, [IDr], SAi2, TSi, TSr, N(EAP_ONLY_AUTHENTICATION), [CP(CFG_REQUEST)] } -->	<-- HDR, SK { IDr, EAP(Request) }
HDR, SK { EAP(Response) } -->	<-- HDR, SK { EAP(Request) }
HDR, SK { EAP(Response) } -->	<-- HDR, SK { EAP(Success) }
HDR, SK { AUTH } -->	<-- HDR, SK { AUTH, SAr2, TSi, TSr, [CP(CFG_REPLY)] }

Note: all notation in the above protocol sequence and elsewhere in this specification is as defined in [RFC4306], and see in particular Sec. 1.2 of [RFC4306] for payload types.

The NAT detection and Configuration payloads are shown for informative purposes only; they do not change how EAP authentication works.

An IKE SA that was set up with this extension can be resumed using the mechanism described in [RFC5723]. However, session resumption does not change the authentication method. Therefore, during the IKE\_AUTH exchange of the resumed session, this extension MUST NOT be sent by the initiator.

#### 4. Safe EAP Methods

EAP methods to be used with this extension MUST have the following properties:

1. The method provides mutual authentication of the peers.
2. The method is key-generating.
3. The method is resistant to dictionary attacks.

The authors believe that the following EAP methods are secure when used with the current extension. The list is not inclusive, and there are likely other safe methods that have not been listed here.

Method Name	Allows Channel Binding?	Reference
EAP-SIM	No	[RFC4186]
EAP-AKA	Yes	[RFC4187]
EAP-AKA'	Yes	[RFC5448]
EAP-GPSK	Yes	[RFC5433]
EAP-pwd	No	[RFC5931]
EAP-EKE	Yes	[EMU-EAP-EKE]
EAP-PAX	Yes	[RFC4746]
EAP-SAKE	No	[RFC4763]
EAP-SRP	No	[EAP-SRP]
EAP-POTP (mutual authentication variant)	Yes	[RFC4793]
EAP-TLS	No	[RFC5216]
EAP-FAST	No	[RFC4851]
EAP-TTLS	No	[RFC5281]

The "Allows channel binding?" column denotes protocols where protected identity information may be sent between the EAP endpoints. This third, optional property of the method provides protection against certain types of attacks (see Section 6.2 for an explanation), and therefore in some scenarios, methods that allow for channel binding are to be preferred. It is noted that at the time of writing, even when such capabilities are provided, they are not fully specified in an interoperable manner. In particular, no RFC specifies what identities should be sent under the protection of the channel binding mechanism, or what policy is to be used to correlate identities at the different layers.



## 5. IANA Considerations

This document defines a new IKEv2 Notification Payload type, EAP\_ONLY\_AUTHENTICATION, described in Section 3. This payload has been assigned the type number 16417 from the "Status Types" range.

## 6. Security Considerations

Security considerations applicable to all EAP methods are discussed in [RFC3748]. The EAP Key Management Framework [RFC5247] deals with issues that arise when EAP is used as a part of a larger system.

### 6.1. Authentication of IKEv2 SA

It is important to note that the IKEv2 SA is not authenticated by just running an EAP conversation: the crucial step is the AUTH payload based on the EAP-generated key. Thus, EAP methods that do not provide mutual authentication or establish a shared secret key MUST NOT be used with the modifications presented in this document.

### 6.2. Authentication with Separated IKEv2 Responder / EAP Server

As described in Section 2, the EAP conversation can terminate either at the IKEv2 responder or at a backend AAA server.

If the EAP method is terminated at the IKEv2 responder, then no key transport via the AAA infrastructure is required. Pre-shared secret and public-key-based authentication offered by IKEv2 is then replaced by a wider range of authentication and key exchange methods.

However, typically EAP will be used with a backend AAA server. See [RFC5247] for a more complete discussion of the related security issues; here we provide only a short summary.

When a backend server is used, there are actually two authentication exchanges: the EAP method between the client and the AAA server, and another authentication between the AAA server and IKEv2 gateway. The AAA server authenticates the client using the selected EAP method, and they establish a session key. The AAA server then sends this key to the IKEv2 gateway over a connection authenticated using, e.g., IPsec or Transport Layer Security (TLS).

Some EAP methods do not have any concept of pass-through authenticator (e.g., Network Access Server (NAS) or IKEv2 gateway) identity, and these two authentications remain quite independent of each other. That is, after the client has verified the AUTH payload sent by the IKEv2 gateway, it knows that it is talking to SOME gateway trusted by the home AAA server, but not which one. The

situation is somewhat similar if a single cryptographic hardware accelerator, containing a single private key, would be shared between multiple IKEv2 gateways (perhaps in some kind of cluster configuration). In particular, if one of the gateways is compromised, it can impersonate any of the other gateways towards the user (until the compromise is discovered and access rights revoked).

In some environments it is not desirable to trust the IKEv2 gateways this much (also known as the "Lying NAS Problem"). EAP methods that provide what is called "connection binding" or "channel binding" transport some identity or identities of the gateway (or WLAN access point / NAS) inside the EAP method. Then the AAA server can check that it is indeed sending the key to the gateway expected by the client. A potential solution is described in [EAP-SERVICE], see also [EMU-AAAPAY].

In some deployment configurations, AAA proxies may be present between the IKEv2 gateway and the backend AAA server. These AAA proxies MUST be trusted for secure operation, and therefore SHOULD be avoided when possible; see Section 2.3.4 of [RFC4072] and Section 4.3.7 of [RFC3579] for more discussion.

### 6.3. Protection of EAP Payloads

Although the EAP payloads are encrypted and integrity protected with SK\_e/SK\_a, this does not provide any protection against active attackers. Until the AUTH payload has been received and verified, a man-in-the-middle can change the KEi/KEr payloads and eavesdrop or modify the EAP payloads.

In IEEE 802.11i wireless LANs, the EAP payloads are neither encrypted nor integrity protected (by the link layer), so EAP methods are typically designed to take that into account.

In particular, EAP methods that are vulnerable to dictionary attacks when used in WLANs are still vulnerable (to active attackers) when run inside IKEv2.

The rules in Section 4 are designed to avoid this potential vulnerability.

#### 6.4. Identities and Authenticated Identities

When using this protocol, each of the peers sends two identity values:

1. An identity contained in the IKE ID payload.
2. An identity transferred within the specific EAP method's messages.

(IKEv2 omits the EAP Identity request/response pair, see Section 3.16 of [RFC5996].) The first identity value can be used by the recipient to route AAA messages and/or to select authentication and EAP types. But it is only the second identity that is directly authenticated by the EAP method. The reader is referred to Section 2.16 of [RFC5996] regarding the need to base IPsec policy decisions on the authenticated identity. In the context of the extension described here, this guidance on IPsec policy applies both to the authentication of the client by the gateway and vice versa.

#### 6.5. User Identity Confidentiality

IKEv2 provides confidentiality for the initiator identity against passive eavesdroppers, but not against active attackers. The initiator announces its identity first (in message 3), before the responder has been authenticated. The usage of EAP in IKEv2 does not change this situation, since the ID payload in message 3 is used instead of the EAP Identity Request/Response exchange. This is somewhat unfortunate since when EAP is used with public key authentication of the responder, it would be possible to provide active user identity confidentiality for the initiator.

IKEv2 protects the responder's identity even against active attacks. This property cannot be provided when using EAP. If public key responder authentication is used in addition to EAP, the responder reveals its identity before authenticating the initiator. If only EAP is used (as proposed in this document), the situation depends on the EAP method used (in some EAP methods, the server reveals its identity first).

Hence, if active user identity confidentiality for the responder is required then EAP methods that offer this functionality have to be used (see [RFC3748], Section 7.3).

## 7. Acknowledgments

This document borrows some text from [RFC3748], [RFC4306], and [RFC4072]. We would also like to thank Hugo Krawczyk for interesting discussions about this topic, Dan Harkins, and David Harrington for their comments.

## 8. References

### 8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC3748] Aboba, B., Blunk, L., Vollbrecht, J., Carlson, J., and H. Levkowitz, "Extensible Authentication Protocol (EAP)", RFC 3748, June 2004.
- [RFC4306] Kaufman, C., "Internet Key Exchange (IKEv2) Protocol", RFC 4306, December 2005.
- [RFC5723] Sheffer, Y. and H. Tschofenig, "Internet Key Exchange Protocol Version 2 (IKEv2) Session Resumption", RFC 5723, January 2010.
- [RFC5996] Kaufman, C., Hoffman, P., Nir, Y., and P. Eronen, "Internet Key Exchange Protocol Version 2 (IKEv2)", RFC 5996, September 2010.

### 8.2. Informative References

- [EAP-SERVICE] Arkko, J. and P. Eronen, "Authenticated Service Information for the Extensible Authentication Protocol (EAP)", Work in Progress, October 2005.
- [EAP-SRP] Carlson, J., Aboba, B., and H. Haverinen, "EAP SRP-SHA1 Authentication Protocol", Work in Progress, July 2001.
- [EMU-AAAPAY] Clancy, C., Lior, A., Zorn, G., and K. Hoepfer, "EAP Method Support for Transporting AAA Payloads", Work in Progress, May 2010.
- [EMU-EAP-EKE] Sheffer, Y., Zorn, G., Tschofenig, H., and S. Fluhrer, "An EAP Authentication Method Based on the EKE Protocol", Work in Progress, August 2010.

- [IEEE80211i] Institute of Electrical and Electronics Engineers, "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless Medium Access Control (MAC) and Physical Layer (PHY) specifications: Amendment 6: Medium Access Control (MAC) Security Enhancements", IEEE Standard 802.11i-2004, July 2004.
- [IEEE8021X] Institute of Electrical and Electronics Engineers, "Local and Metropolitan Area Networks: Port-Based Network Access Control", IEEE Standard 802.1X-2001, 2001.
- [RFC1661] Simpson, W., "The Point-to-Point Protocol (PPP)", STD 51, RFC 1661, July 1994.
- [RFC3579] Aboba, B. and P. Calhoun, "RADIUS (Remote Authentication Dial In User Service) Support For Extensible Authentication Protocol (EAP)", RFC 3579, September 2003.
- [RFC4072] Eronen, P., Hiller, T., and G. Zorn, "Diameter Extensible Authentication Protocol (EAP) Application", RFC 4072, August 2005.
- [RFC4186] Haverinen, H. and J. Salowey, "Extensible Authentication Protocol Method for Global System for Mobile Communications (GSM) Subscriber Identity Modules (EAP-SIM)", RFC 4186, January 2006.
- [RFC4187] Arkko, J. and H. Haverinen, "Extensible Authentication Protocol Method for 3rd Generation Authentication and Key Agreement (EAP-AKA)", RFC 4187, January 2006.
- [RFC4746] Clancy, T. and W. Arbaugh, "Extensible Authentication Protocol (EAP) Password Authenticated Exchange", RFC 4746, November 2006.
- [RFC4763] Vanderveen, M. and H. Soliman, "Extensible Authentication Protocol Method for Shared-secret Authentication and Key Establishment (EAP-SAKE)", RFC 4763, November 2006.
- [RFC4793] Nystroem, M., "The EAP Protected One-Time Password Protocol (EAP-POTP)", RFC 4793, February 2007.

- [RFC4851] Cam-Winget, N., McGrew, D., Salowey, J., and H. Zhou, "The Flexible Authentication via Secure Tunneling Extensible Authentication Protocol Method (EAP-FAST)", RFC 4851, May 2007.
- [RFC5216] Simon, D., Aboba, B., and R. Hurst, "The EAP-TLS Authentication Protocol", RFC 5216, March 2008.
- [RFC5247] Aboba, B., Simon, D., and P. Eronen, "Extensible Authentication Protocol (EAP) Key Management Framework", RFC 5247, August 2008.
- [RFC5281] Funk, P. and S. Blake-Wilson, "Extensible Authentication Protocol Tunneled Transport Layer Security Authenticated Protocol Version 0 (EAP-TTLSv0)", RFC 5281, August 2008.
- [RFC5433] Clancy, T. and H. Tschofenig, "Extensible Authentication Protocol - Generalized Pre-Shared Key (EAP-GPSK) Method", RFC 5433, February 2009.
- [RFC5448] Arkko, J., Lehtovirta, V., and P. Eronen, "Improved Extensible Authentication Protocol Method for 3rd Generation Authentication and Key Agreement (EAP-AKA')", RFC 5448, May 2009.
- [RFC5931] Harkins, D. and G. Zorn, "Extensible Authentication Protocol (EAP) Authentication Using Only A Password", RFC 5931, August 2010.

## Appendix A. Alternative Approaches

In this section, we list alternatives that have been considered during the work on this document. We concluded that the solution presented in Section 3 seems to fit better into IKEv2.

### A.1. Ignore AUTH Payload at the Initiator

With this approach, the initiator simply ignores the AUTH payload in message 4 (but obviously must check the second AUTH payload later!). The main advantage of this approach is that no protocol modifications are required and no signature verification is required. A significant disadvantage is that the EAP method to be used cannot be selected to take this behavior into account.

The initiator could signal to the responder (using a notification payload) that it did not verify the first AUTH payload.

### A.2. Unauthenticated Public Keys in AUTH Payload (Message 4)

Another solution approach suggests the use of unauthenticated public keys in the public key signature AUTH payload (for message 4).

That is, the initiator verifies the signature in the AUTH payload, but does not verify that the public key indeed belongs to the intended party (using certificates) -- since it doesn't have a PKI that would allow this. This could be used with X.509 certificates (the initiator ignores all other fields of the certificate except the public key), or "Raw RSA Key" CERT payloads.

This approach has the advantage that initiators that wish to perform certificate-based responder authentication (in addition to EAP) may do so, without requiring the responder to handle these cases separately. A disadvantage here, again, is that the EAP method selection cannot take into account the incomplete validation of the responder's certificate.

If using RSA, the overhead of signature verification is quite small, compared to the  $g^{xy}$  calculation required by the Diffie-Hellman exchange.

### A.3. Using EAP Derived Session Keys for IKEv2

It has been proposed that when using an EAP method that provides mutual authentication and key agreement, the IKEv2 Diffie-Hellman exchange could also be omitted. This would mean that the session keys for IPsec SAs established later would rely only on EAP-provided keys.

It seems the only benefit of this approach is saving some computation time ( $g^{xy}$  calculation). This approach requires designing a completely new protocol (which would not resemble IKEv2 anymore); we do not believe that it should be considered. Nevertheless, we include it for completeness.

#### Authors' Addresses

Pasi Eronen  
Independent

E-Mail: [pe@iki.fi](mailto:pe@iki.fi)

Hannes Tschofenig  
Nokia Siemens Networks  
Linnoitustie 6  
Espoo 02600  
Finland

Phone: +358 (50) 4871445  
E-Mail: [Hannes.Tschofenig@gmx.net](mailto:Hannes.Tschofenig@gmx.net)  
URI: <http://www.tschofenig.priv.at>

Yaron Sheffer  
Independent

E-Mail: [yarof.ietf@gmail.com](mailto:yarof.ietf@gmail.com)